

5.000 - 11.000 l/h Discs, cartridges, bag

Typical applications
Plating and process industry

Features

- Service friendly, ideal cleaning access height
- Magnetic drive or mechanical seal pump
- Filter chamber with welded bottom (no seal)
- Discs (thin/thick paper, cloth), cartridges or pleated bag
- All PP or PVDF construction
- Max. temperature PP 80°C / PVDF 100°C
- Bottom-out or top-out model
- Choice of slurry tank for carbon treatment, mixing and priming
- Unions for rigid piping (PP, PVDF or CPVC sockets)
- Standard with 3 phase motor, thermal overload switch, lead without plug, pressure gauge, air release and drain valve

Options

- Hose connection
- Dry run protection
- By pass with flowmeter
- Contact manometer
- Single open end cartridges



MX60-71A-K-PP



MX90-72A-P-S-PP

Filter Systems series 7

i www.hendor.com

Pump	l/h	kW	Union (d/DN) In Out	Hose In Out	Type	Chamber	Medium	Slurrytank	Material
Magnetic drive (PP/PVDF)	5000	0,25*	32/25 32/25	1 1/4" 1 1/4"	MX60	71A 72A ↑ ↓	K/P		PP-EPDM
	8000	0,37*	40/32 32/25	1 1/2" 1 1/4"	MX90				
	10000	0,55	40/32 32/25	1 1/2" 1 1/4"	MX120				
Mechanical seal (PP only)	5000	0,55	32/25 32/25	1 1/4" 1 1/4"	S055	71 72 ↑ ↓	K/P/D	10 liter 21 liter	PVDF-Viton
	8000	0,75	40/32 32/25	1 1/2" 1 1/4"	S075				
	11000	1,1	40/32 32/25	1 1/2" 1 1/4"	S110				

Selection: MX60 71A K PP

K = cartridges

Qty x L
71 (A)-K = 7 x 10"
72 (A)-K = 7 x 20"

P = discs

Qty	OD/ID	m²
71-P = 37 x 205/32	1,2	
72-P = 69 x 205/32	2,2	
71A-P = 32 x 205/32	1,0	
72A-P = 65 x 205/32	2,1	

D = pleated bag

L	m²
71-D = 10"	0,8
72-D = 20"	1,4

* For 3-phase motors < 220V the indicated motor will be one size bigger.